

Application Number: 10/718,649

2001P80072WOUS  
Christian Weis**AMENDMENTS TO THE CLAIMS**

The text of all pending claims, (including withdrawn claims) is set forth below. The following listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. - 7. (cancelled).

8. (previously presented) The device according to claim 21, wherein said gear ring and hub comprise a plastic and said intermediate element comprises an elastic plastic.

9. (previously presented) The apparatus device to claim 21, wherein the control disk comprises means for effecting a locking and a releasing of the control disk.

10. - 14. (cancelled)

15. (previously presented) The device according to claim 21, wherein said locking element is part of a door lock of said motor vehicle.

16. (previously presented) The device according to claim 21, further comprising at least one arm mechanically coupled to said control disk, said at least one arm facilitating imparting of a drive force on said locking element from said control disk.

17. (previously presented) The device according to claim 16, wherein said at least one arm comprises two arms mechanically linked via a single rotatable shaft, and said two arms are spring biased to said control disk.

18. (previously presented) The device according to claim 17, wherein said control disk comprises a plurality of tracks, and said two arms further comprise end extensions engaging said tracks.

19. (previously presented) The device according to claim 18, wherein two of said plurality of tracks are located on opposite sides of said control disk.

20. (previously presented) The device according to claim 21, further comprises a first and a second stop element, said first stop element located at a circumferential location of said control disk and said second stop element located in a path of movement of said first stop element so as to engage said first stop element,

Application Number: 10/718,649

2001P80072WOUS  
Christian Weis

wherein when said first stop and second stop elements engage on another said control disk is halted in a direction of said path of movement.

21. (currently amended) An electronically driven locking device for electronically engaging and disengaging a locking element of a motor vehicle, wherein the locking device including is coupled to

—actuating means having a motor and a worm gear, said motor arranged to drive said worm gear and generate kinetic energy resulting in application of a torque to said locking device, said locking device comprising:

- a gear wheel comprising a gear ring, a hub, ~~and an elastic intermediate element and a central axis upon which the gear ring, hub and elastic intermediate element are arranged,~~

- wherein each one of said gear ring, hub and elastic intermediate element has a lateral side that is substantially perpendicular to said central axis,

- wherein said gear wheel, gear ring and hub being are joined together by said elastic intermediate element and said gear wheel and hub being further joined together via a material to material bond, so that the intermediate element is sandwiched between a lateral side of the gear ring and a lateral side of the hub,

- wherein said gear ring and hub each comprising comprise circumferential teeth, said gear ring teeth being arranged to engage said worm gear such that force from said worm gear is imparted upon said gear ring, wherein the gear wheel comprises a central axis upon which the gear ring, hub and intermediate element are arranged such that the intermediate element is sandwiched between sides of the gear ring and hub, and

- a control disk comprising circumferential gears arranged to interact with said hub gears such that rotational force may be exchanged between said control disk and hub, said control disk mechanically linked to said locking element such that said torque is absorbed by said intermediate element.

Application Number: 10/718,649

2001P80072WOUS  
Christian Weis

22. (previously presented) The drive element according to claim 21, wherein said torque comprises kinetic energy with said device after deactivation of said motor.

23. (cancelled)

24. (cancelled)